
Common Mode Filters For Automotive Signal Line
Size 3225




-
-
-
-
-
-

℃


Dimensions: [mm]



Land Pattern: [mm]




Schematic:




Electrical Properties:


Part No	Z@10MHz Min	Z@10MHz Typ	L @ 100kHz/0.1V	Tol.	I_R Max.	R_{DC} Max.	V_{DC} Max. (V	IR Min

Typical Electrical Characteristics:






Reel Dimension：[mm]



Packaging Quantity:



1000 Pcs/Reel

5 Reel /Inner box(5000 Pcs)

8 Inner box/Carton box(40K Pcs)

Cautions and Warnings:

Storage Conditions：

- The storage period is within 12 months after the completion of production. Be sure to follow the storage conditions (temperature: -5 to 35°C, humidity: 75% RH Max).If the storage period elapses, the soldering of the terminal electrodes may deteriorate.
- Product should not be exposed to environment with high temperature, high humidity, dust, corrosive gas and etc.
- Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- Please always handle products carefully to prevent any damage caused by dropping down or inappropriate removing.

Operation Instructions:

- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- Before soldering, be sure to preheat components.The preheating temperature should be set so that the temperature difference between the solder temperature and chip temperature does not exceed 150°C.
- Soldering corrections after mounting should be within the range of the conditions determined in the specifications.If overheated, a short circuit, performance deterioration, or lifespan shortening may occur.
- Generally, Koher might not be familiar with either customer's specific application or actual requests as customer does.As a result customer shall be responsible for checking and confirming whether Koher product with the performance described in the product specification is suitable for using in customer's particular application or not.