MDTA Series

Flat Wire Molded Inductor

Size 1580



FEATURES


-
-
-
-
-
-
-

℃


APPLICATION

-
-

Dimensions: [mm]



Land Pattern: [mm]



Electrical Properties:

Saturation Current will cause L to drop approximately 30%


Temperature Rise Current that causes the specified temperature rise from 25°C ambient.

KOHER Electronic

4546 BATES DRIVE, YORBLINDA CA 92886 USA

714-325-4789 Contact@kohergroup.com

Soldering Reflow:



Preheat condition: 150 ~200℃/ 60~120 sec.

Allowed time above 217℃: 60~90 sec.


Max temperature: 260℃.

Max time at max temperature: 10 sec.

Allowed Reflow time: 2x max.


Packaging Information:

Tape Dimension:



Series	A0 (mm)	B0 (mm)	D (mm)	P0 (mm)	P1 (mm)	W (mm)	K0 (mm)	E (mm)	T (mm)
MDTA1580	17.0±0.1	16.0±0.1	1.5±0.1	4.0±0.1	24.0±0.1	32.0±0.3	8.5±0.1	1.75±0.1	0.50±0.05

Peel force of top cover tape:




The peel force of top cover tape shall be between 0.1 to 1.3 N

Product Marking:

Marking	Printing (Inductance)

Reel Dimension：[mm]



Packaging Quantity: